

4' Horizontal Display Case LED Retrofit Lamp

18 Watt - 180° A-B-C Type



BENEFITS

- Milky lens for NO glare, NO hot spots
- IP67 rated - for wet locations
- Magnet mounted for quick installation!
- Greater than 95 CRI
- Premium visual merchandising
- Superior luminance and low power consumption
- 180 Degree Beam Angle
- No UV, No RF interference
- No Mercury, RoHS compliant

4' 180° 18W Horz. Display Case Lamp

SKU options:

GL-180-4F-18W-95-3000K-A-IP67 180° A-Type Fixture
 GL-180-4F-18W-95-3000K-B-IP67 180° B-Type Fixture
 GL-180-4F-18W-95-3000K-C-IP67 180° C-Type Fixture


GL-180-4F-18W-95-3500K-A-IP67 180° A-Type Fixture
 GL-180-4F-18W-95-3500K-B-IP67 180° B-Type Fixture
 GL-180-4F-18W-95-3500K-C-IP67 180° C-Type Fixture

GL-180-4F-18W-95-4000K-A-IP67 180° A-Type Fixture
 GL-180-4F-18W-95-4000K-B-IP67 180° B-Type Fixture
 GL-180-4F-18W-95-4000K-C-IP67 180° C-Type Fixture



SPECIFICATIONS

average wattage	18 watts (ea.)
luminous efficacy	85 lm/W (ea.)
input voltage	95-305 VAC
color temp (ANSI)	3000K, 3500K, 4000K
CRI (color rendering index)	>95
R9	>85
system input current	24 Volt DC Constant Voltage
output	1,530 lumens (ea.)
beam angle	180 degrees
dimensions	1168mm x 50mm (ea.)
life span	> 100,000 hours
operating temperature (driver)	-22F +86F (-30C +30C)
ratings	IP67
warranty	7 years non-prorated
certification	ETL, c CSA us, UL1598, UL 8750, NSF, DLC (pending)
driver	Custom UL Class 2
power factor	1.00
total harmonic distortion	10%
off-state power	0 watts



ledgreenlightint.com

Products are warranted only to meet LED Greenlight International's production data sheet specifications. Products and specifications are subject to change without notice.

rev 9-08-2015



4115 Challenger Way, Caldwell, ID 83605