

Refrigerated Vertical Case 6' 180° LED 16 Watt



BENEFITS

- Magnet mounted for quick installation!
- Milky lens for NO glare, NO hot spots
- Ultra-slim profile
- CRI Greater than > 94
- Premium visual merchandising
- IP67 rated (damp and wet locations)
- High luminance and low power consumption
- 180 Degree Beam Angle
- No UV, No RF interference
- No Mercury, RoHS compliant

LED Greenlight 16 Watt Vertical Lamp

SKU options:

- GL-180-6F-16W-94-3000K-IP67
- GL-180-6F-16W-94-3500K-IP67
- GL-180-6F-16W-94-4000K-IP67



ledgreenlightint.com

Products are warranted only to meet LED Greenlight International's production data sheet specifications. Products and specifications are subject to change without notice.

rev 10-20-2015

SPECIFICATIONS

average wattage	16 watts
luminous efficacy	136 lm/W
input voltage	95 -305 VAC
color temp (ANSI)	3000K, 3500K, 4000K
CRI (color rendering index)	94
R9	>75
system input current	24 Volt DC Constant Voltage
output	2,176 lumens (clear), 2,000 (milky)
beam angle	180 degrees
dimensions	1829mm x 50mm
life span	> 100,000 hours
operating temperature (driver)	-22F +86F (-30C +30C)
ratings	IP67
warranty	7 years non-prorated
certification	c CSA us, UL1598, UL 8750, NSF, DLC (pending)
driver	Custom UL Class 2
power factor	1.00
total harmonic distortion	10%
off-state power	0 watts



4115 Challenger Way, Caldwell, ID 83605