

Refrigerated Vertical Case 6' 90° LED 8 Watt



BENEFITS

- Magnet mounted for quick installation!
- Milky lens for NO glare, NO hot spots
- Ultra-slim profile
- CRI Greater than > 94
- Premium visual merchandising
- IP67 rated (damp and wet locations)
- High luminance and low power consumption
- 90° Beam Angle
- No UV, No RF interference
- No Mercury, RoHS compliant

LED Greenlight 8 Watt 90° Vertical Case Lamp

SKU options:

- GL-90-6F-8W-94-3000K-IP67
- GL-90-6F-8W-94-3500K-IP67
- GL-90-6F-8W-94-4000K-IP67



ledgreenlightint.com

Products are warranted only to meet LED Greenlight International's production data sheet specifications. Products and specifications are subject to change without notice.

rev 10-20-2015

SPECIFICATIONS

| | |
|--------------------------------|---|
| average wattage | 8 watts |
| luminous efficacy | 136 lm/W |
| input voltage | 95 -305 VAC |
| color temp (ANSI) | 3000K, 3500K, 4000K |
| CRI (color rendering index) | 94 |
| R9 | >75 |
| system input current | 24 Volt DC Constant Voltage |
| output | 1,088 lumens (clear), 1,000 (milky) |
| beam angle | 90 degrees |
| dimensions | 1829mm x 25mm |
| life span | > 100,000 hours |
| operating temperature (driver) | -22F +86F (-30C +30C) |
| ratings | IP67 |
| warranty | 7 years non-prorated |
| certification | c CSA us, UL1598, UL 8750, NSF, DLC (pending) |
| driver | Custom UL Class 2 |
| power factor | 1.00 |
| total harmonic distortion | 10% |
| off-state power | 0 watts |



4115 Challenger Way, Caldwell, ID 83605